



**EATON 10HP 1PH 39CFM FIXED SPEED INDUSTRIAL ROTARY SCREW COMPRESSOR MOUNTED ON A 120 GAL HORIZONTAL TANK SWINGARM 58CFM AIR DRYER**

**SKU:** PRI010S120V |



**Brands**

**EATON COMPRESSOR**

Got Questions ? Call us! 888-954-9293



|                                    |            |
|------------------------------------|------------|
| <b>HP</b>                          | 10         |
| <b>Tank Size</b>                   | 120        |
| <b>Voltage +/- 10%</b>             | 230        |
| <b>Phase</b>                       | 1          |
| <b>Drive Type</b>                  | Electric   |
| <b>Tank Drain</b>                  | Automatic  |
| <b>CFM</b>                         | 39.90      |
| <b>Silent Air</b>                  | N          |
| <b>Smart Air</b>                   | N          |
| <b>Compressor Type</b>             | ROTARY     |
| <b>Motor Type</b>                  | ODP        |
| <b>Tank Orientation</b>            | Horizontal |
| <b>Belt Count</b>                  | 2          |
| <b>Pump Stage</b>                  | 1          |
| <b>Pump Riser</b>                  | N          |
| <b>Belt Tensioner</b>              | N          |
| <b>Mag Starter</b>                 | N          |
| <b>Radiator</b>                    | N          |
| <b>Peak Starting Amps</b>          | 0.00       |
| <b>Pump RPM</b>                    | 0.00       |
| <b>Motor RPM</b>                   | 1750.00    |
| <b>FLA + 1.15 Service Factor</b>   | 38.30      |
| <b>Locked Rotor Amps</b>           | 0.00       |
| <b>Recommended Breaker</b>         | 55.00      |
| <b>Max PSI</b>                     | 145.00     |
| <b>Uncrated Weight</b>             | 0.00       |
| <b>Crated Weight</b>               | 1393.00    |
| <b>Crated Length</b>               | 85         |
| <b>Crated Width</b>                | 50         |
| <b>Crated Height</b>               | 80         |
| <b>Oil Capacity</b>                | 1.33       |
| <b>Oil U/M</b>                     | Gallons    |
| <b>Estimated Pump Life (Hours)</b> | 60000.00   |
| <b>Certifications</b>              | UL/CSE     |
| <b>Service Kit</b>                 | SKIT001AWB |
| <b>Battery Voltage</b>             | 0.00       |
| <b>DBA</b>                         | 0.00       |
| <b>Max Ambient Temp (F°)</b>       | 0.00       |
| <b>Max Inlet Temp (F)</b>          | 0.00       |