

## 40-60HP Standard Speed Drive Rotary Screw Air System

- Our Y/Delta Soft Start limits the voltage on startup, making ours one of the most energy-efficient rotary screw compressors on the market
- Precision-engineered Tamrotor/Gardner Denver rotary air end is covered by a 10 year warranty
- Premium industrial motor carries a 5 year warranty on single phase & 10 year on three phase
- 5 year warranty on remaining components, less wear parts
- PLC controller monitors maintenance, temperature, oil level, filtration, hours, plus remote start/stop, timed start/stop & automatic restart
- Ultra-quiet operation with heavy-duty soundproof panels
- Reduces energy demand up to 33%
- Schneider internal electrical circuit
- Direct drive lessens the load on the pump and motor drive bearings, requiring no belt maintenance
- VMC inlet valve and load solenoid
- Schneider Y/Delta magnetic contactors UL/CSA listed
- 70,000 + running hours

•	EXTON COMPRESSOR INDUSTRIAL AIR TECHNOLOGY
1	·

	PRS0400003D	PRS0500003D	PRS0600003D
Running HP	40	50	60
CFM 100 PSI	188	235	261
Max PSI	145	145	145
Drive Type	Direct Drive	Direct Drive	Direct Drive
Motor RPM	1750	1750	1750
Airend Model	GD Enduro 12G	GD Enduro 12G	GD Enduro 12G
Start Type	Y/Delta Soft Start	Y/Delta Soft Start	Y/Delta Soft Start
Outlet Size	1 1/4" NPT	1 1/4" NPT	1 1/4" NPT
Motor Phase	Three	Three	Three
Noise DBA	79	79	79
Dimensions	66.5" L x 49.5" W x 65" H	66.5" H x 49.5" W x 65" D	66.5" H x 49.5" W x 65" D
Weight	2,220 lbs	2,350 lbs	2,450 lbs







<sup>\*10</sup> year warranty is only valid with annual purchase of service kit