

7.5HP Standard Speed Rotary Screw Air Compressor with Dryer Package

- Our Wye Delta Soft Start limits the voltage on startup, making ours one of the most energy-efficient rotary screw compressors on the market
- Precision-engineered rotary air end is covered by a 10 year warranty*
- Premium industrial motor carries a 5 year warranty on single phase & 10 year on three phase
- 5 year warranty on remaining components, less wear parts
- PLC Controller monitors maintenance, temperature, oil level, filtration, hours, plus remote start/stop, timed start/stop and automatic restart
- Ultra-quiet operation with heavy-duty soundproof panels
- Reduces energy demand up to 33%
- Schneider magnetic contactors are UL/CSA listed
- VMC inlet valve and load solenoid
- 70,000 + running hours



	PRS007PKG1	PRS007PKG3
Running HP	7.5	7.5
CFM 100 PSI	29	29
Max PSI	145	145
Drive Type	Belt	Belt
Motor RPM	1750	1750
Motor Efficiency	Premium Class	Premium Class
Motor Frame Size	213~T	213~T
Voltage	208/230/460	208/230/460
Enclosure	TEFC	TEFC
Airend Model	Rotorcomp Evo2	Rotorcomp Evo2
Start Type	Wye Delta Soft Start	Wye Delta Soft Start
Outlet Size	3/4" NPT	3/4" NPT
Motor Phase	Single	Three
Noise DBA	62	62
Tank Size	120 Gallon	120 Gallon
Cabinet Dimensions	32 5/8"L x 24"W x 41 3/8"H	32 5/8"L x 24"W x 41 3/8"H
Cabinet Weight	660 lbs	660 lbs
Tank Dimensions	36" x 32" x 54"	36" x 32" x 54"
Tank Weight	330 lbs	330 lbs

DRYER SPECIFICATIONS	
Dryer CFM	29 CFM
Dryer Orientation	Vertical
Dryer Drain	Built-in Timed Automatic
Dryer filtration	Prefilter & Coalescing Filter
Connection Size	1/2"
Max Ambient Temp	122°
Max Rated Inlet Temp	140°
Voltage	115
Refrigerant Type	R134a
Dew Point	37° - 50°
Cabinet Dimensions	

*10 year warranty is only valid with annual purchase of service kit

